



# JL-12 Lubricant

## Product Description

An opaque, gelled, metal forming lubricant which clings to tool surfaces and dissipates to a clean, light residual. It is a clean soap based product designed to “stay where it is applied”. It will substantially reduce consumption and improve housekeeping and tool life.

## Typical Properties

Appearance ..... Opaque gel  
Density..... 7.9 lbs./gallon

## Application

Designed for metalworking applications such as tube bending and draw forming.

## Use Directions

Metal Mates JL-12 Lubricant is supplied ready to use. Note: minimal amounts can be used when compared to conventional lubricants because it stays where it is applied.

## Advantages

- Easily cleaned
- No drip “stays where applied”
- Weldable with low smoke
- Clean
- Contains no petroleum or pigments
- Will not buildup

## Safety and Handling

Avoid contact with eyes and prolonged contact with the skin. Wash thoroughly after handling. Minimum contact with this and all chemicals is a good policy to follow along with reading the Material Safety Data Sheet.

## Storage

Indoor storage preferred. First in first out stock rotation is recommended. If frozen, allow to thaw then mix thoroughly.

## Container Size

5 gallon pails, 55 gallon drums and 330 gallon totes.

**TW** **ROCOL® North America**

3624 West Lake Avenue · Glenview, IL 60026

Tel (800) 452-5823 · Fax (800) 952-5823

Tel (800) 657-5278 · Fax (800) 657-4897

[www.rocolnorthamerica.com](http://www.rocolnorthamerica.com)