



WL Lubricant

Product Description

A universal lubricant designed to keep dies and metal surfaces clean for stamping, drawing, piercing and roll forming. This water based lubricant is ideal for light to medium forming that requires clean surfaces. This product contains additives for corrosion protection and bacterial prevention.

Typical Properties

Appearance Milky liquid
Solubility Emulsifiable with water
Density 8.1 lbs/gallon

Application

Spray, brush, roll coat, blank wash, or drip on the following substrates: cold/hot rolled steel, hot dip/EG galvanized, stainless steel and aluminum.

Use Directions

Metal Mates WL can be diluted with water. Mixing Instructions: Slowly add water to lubricant while mixing.

Safety and Handling

Avoid contact with eyes and prolonged contact with the skin. Wash thoroughly after handling. Minimum contact with this and all chemicals is a good policy to follow along with reading the Material Safety Data Sheet.

Storage

Indoor storage preferred. First in first out stock rotation is recommended. If frozen, allow to thaw then mix thoroughly.

Container Size

5 gallon pails, 55 gallon drums and 330 gallon totes.

TW **ROCOL® North America**

3624 West Lake Avenue · Glenview, IL 60026

Tel (800) 452-5823 · Fax (800) 952-5823

Tel (800) 657-5278 · Fax (800) 657-4897

www.rocolnorthamerica.com